



LED-702



LED-712

AVAILABLE OPTIONS





Photo Control





Aluminum anodized arm

Line Drawing



Dimensions



Product Description:

Dusk to Dawn Fixture of the future is here. Utilizing a single source LED, this dusk to dawn provides prismatic-designed light output for any environment. It is optional to add a NEMA approved Photocontrol which used with LED provides significant power savings. Maintaining all the strengths of the traditional dusk to dawn fixtures such as installation brackets and arms while utilizing the latest generation of LEDs, this LED dusk to dawn will last for years to come.

Optional Kelvin color* with adder.

Features:

LISTING

UL and CUL listed for wet locations

HOUSING

Solid construction die-cast aluminum body

FINISH

UV stabilized power coated finish

OPTIONS

Uniform light distribution

Finish - Gray. Color option with adder

Standard Gray

SPECIFICATION

Model No.	LED-702	LED-712	LED-712
System watts	35	40	55
Lumen Output	3680 lm**	4503 lm**	6319 lm**
Color	5000K		
MA	830MA	950MA	1400MA
Input Voltage	120~277V		
CRI	70+		
Starting Temp	-40°C		
Equivalent	100W MH	150W MH	200W MH

* Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.

** DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.